




B-13A

12W

简述 Description



- 铝压铸灯具端盖和安装连接件，造型简洁实用
- 高透明PC扩散罩，能有效防止发黄老化
- 灯具采用间接投射发光模式，具有很好的视觉舒适性
- 高性能LED芯片，驱动有0-10V / DALI / 编程电源选择
- 防紫外线聚氨酯塑料喷涂表面
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

其他功能选项:


移动感应功能 / 双色温切换功能

- Aluminum die casting cover and installation connector, simple and practical shape.
- High transparent PC diffuser, it can effectively prevent yellowing and aging.
- Indirect light luminaire for use with led, which has high visual comfort.
- High quality LED chips, Driver with 0-10V/DALI/programmed options.
- Surface anti-ultraviolet pure polyester powder painting.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

Other Options:

Move sensor options / Colour temperature options

技术参数 Technology data



B-13A

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835							
B-13ALED12-56	12W	56	100V-240V	1080	120°	400*260*200	4

延伸产品 More in family



C-13A

Bollard Lighting: 12W.
Page. 378