



B-12
12W



B-12D
9W*2


简述 Description



- 铝压铸灯体外壳，超白磨砂钢化玻璃，具有很好的光舒适性
- 模组式光源模块，灯具光照角度可调
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达到1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

- Die-casting aluminium body, super white frosted tempered glass, with high visual comfort light distribution.
- LED module design, and the module angle can adjustable.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



B-12

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3030							
B-12LED12-10B	12W	10	100V-240V	1050	85°	305*265*195	4
B-12DLED18-20B	18W	10*2	100V-240V	2100	85°	305*270*380	4

延伸产品 More in family



C-12
Bollard Lighting: 12W.
Page. 376



C-12D
Bollard Lighting: 18W.
Page. 376