




M-16A



M-16A
2W



简述 Description



- 铝压铸灯体外壳，高强度透明玻璃扩散罩
- 侧向发光方式，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、热镀锌安装预埋件
- 根据需要有地板 / 地面 / 墙面嵌入式安装应用
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

- Die-casting aluminium body, high quality pc diffuser.
- Side radial light with bidirectional emission, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, Hot galvanized steel installion housing.
- Floor/ground/wall-mounted recessed luminaire intended applications as required.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.



Ground installation



Floor installation




Wall-mounted installation

光效: 60-70 Lm/W (Ra80)
色温: 3000K / BLUE
Nominal efficacy: 60-70 Lm/W (Ra80)
CCT: 3000K / BLUE

- 应用场合: 适用于庭院、草地、导向灯等景观照明场所
- Applications: It can be used for landscape lighting places such assuch as courtyard, lawn, guide direction lighting, etc.

技术参数 Technology data



M-16A

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - F5 M-16ALED2-16	2W	16	Switch	24V AC/DC	120°	390*235*200/6pcs	5