

### TS-191 Series



TS-191P

# 一体式太阳能庭院灯

## All-in-One Integrated **Smart Solar Street Lighting**


















- 铝压铸灯体外壳, 超白钢化玻璃, 白色塑料反射罩
- 高透光PC透镜,具有高视觉舒适性和均匀配光透镜,供多种不同配光选择
- 高性能LED芯片,驱动有0-10V / DALI / 编程电源选择,20KV浪涌保护器
- 有多种安装支架供选择搭配,形成多款不同外形灯具
- 有侧装和顶装2种安装方式,角度可调,安装管径有Ø60/Ø76mm
- 防紫外线聚氨酯塑粉喷涂表面, 盐雾测试可以达1000小时以上
- 无生物蓝光危害风险,符合EN62471: 2008标准
- 道路灯智能远程控制系统可选,可以与远程管理系统兼容
- 所有外部螺钉均为304不锈钢材质
- With LiFePO<sub>4</sub> battery which usually apply for electric bus.
- Die-casting aluminium body, super white tempered glass, white PC plastic reflector.
- Optics with PC lens with high visual comfortable and uniform lighting distribution, multiple light distribution options.
- High quality LED chips, Driver with 0-10V/DALI/programmed be options, and with surge protection up to 20KV.
- There are a variety of mounting brackets options, form of different shapes of lighitng.
- Top and side fixing, angle can be adjustable, installation tube diameter Ø60/Ø76mm.
- Surface anti-ultravilet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, (no risk linked to infrared, blue light and UV radiation) in accordance with EN 62471:2008. • Street lighting control used with smart control technology. It can be compatible with remote management system.
- All external screws are made of 304 stainless steel.

#### 远程控制系统和智能系统可选

Remote control system & Smart intelligent system availble upon request



节能控制系统 Energy saving with




物联网智能系统 Network for smart intelligent system



遥控器 Remote control



人体感应



**TS-191P** 





# **TS-191** Series

# **All-in-One Integrated Smart Solar Street Lighting**


# Technical Data


### SOLAR-GENERAL


Autonomy Information Working mode : 2 days : 1hrs - 100%, 2hrs - 50%, 8hrs - 20%


Model 灯具型号	Power 功率	Solar PV 太阳能板	LiFePO₄ Battery 电池	Luminous 光通量	LED Chips LED灯珠
TS-191PLED12	12W	18V/25W	154WH/12.8V 12AH	1800 lm	3030*84pcs
TS-191HLED12	12W	18V/25W	154WH/12.8V 12AH	1800 lm	3030*84pcs

### 应用透镜 Optics application









### 产品尺寸 Product dimensions

